



High Speed 24/7

Applications

Electric driven hydraulic pump, usable worldwide 100-253 V / 45-66 Hz, up to 700 bar / 10,000 psi for hydraulic wrenches with single or double acting cylinders.

- Duo- or Quattro version (for 2 or 4 wrenches etc.) optional.
- Robust compact design for use on the roughest construction sites.

Advantages

- Huge oil flow due to intelligent electronic controlling, powerful motor.
- Easiest automatic operation for all cylinder sizes without any manual presetting.
- Ergonomic remote control for manual or automatic operation.

alkitronic® specials


- No magnetic valve control
Powerful but gentle changeover from power stroke to idle stroke, due to direction switch of the drive motor, which guarantees high durability of the equipment.
- Capable of continuous operation - minimal heat generation No oil overheating by the innovative motor drive in combination with the automatic mode. The automatic operation only provides the flow supply with the working pressure necessary for efficient bolting.
- Low running costs Brush-free synchronized motor, maintenance-free and low wear. Usable on all international mains supply without any change.




Technical Data

alkitronic® NOVA with infinitely adjustable pressure setting up to 700 bar / 10,000 psi (700 bar / 10,000 psi max. pressure).

Designation	alkitronic® NOVA
Drive electrical	100-253 V / 45-66 Hz
Nominal capacity	3500 W max.
Oil flow:	
low pressure	15 l/min up to 70 bar
medium pressure	10 l/min up to 180 bar
high pressure	1.5 l/min up to 700 bar
Weight including oil	28,5 kg
Dimensions L x W x H (mm)	350 x 220 x 300
Surrounding temperature	-20 °C up to +50 °C



Connection scheme hydraulic hoses



Delivery range: High pressure hoses (DN 8), Length 5m

alkitronic® NOVA multibox



Robust design with load hooks and handles, certified for crane transportation.



alkitronic® products
Made in Germany by
alki TECHNIK GmbH
Development, Production and
Distribution of Bolting Systems

Unterlettenweg 4
85051 Ingolstadt
Germany

fon +49 841 97499-0
fax +49 841 97499-90

info@alkitronic.com
www.alkitronic.com